

**42032F7S**

**GPD505 VARIABLE SPEED CONSTANTS (HIGH VOLTAGE)**

| G5 CONSTANT | G5 VALUE | G5 CONSTANT | G5 VALUE |
|-------------|----------|-------------|----------|
| NO01        | Note 1   | NO22        | 0080.0   |
| NO02        | 3        | NO33        | 0        |
| NO03        | 420.00   | NO39        | 12       |
| NO04        | 0        | NO50        | 2        |
| NO10        | F        | NO51        | 1        |
| NO12        | 178      | NO55        | 2        |
| NO13        | 420.00   | NO56        | 10.0     |
| NO14        | 060.0    | NO64        | 100      |
| NO15        | 003.0    | NO65        | .3       |
| NO16        | 22.5     | NO67        | .7       |
| NO17        | 001.5    | NO70        | 0        |
| NO18        | 12.5     | NO71        | 200      |
| NO19        | 0035.0   | NO72        | 200      |
| NO20        | 20       | NO80        | 50       |
| NO21        | 0120.0   |             |          |

| MOTOR WIRING |            |
|--------------|------------|
| Voltage      | Connection |
| 200 - 240    | A          |
| 380 - 480    | C          |

Note 1: Put in 8 to initialize to 2 wire control

Put in 3 to program

Put in 0 to lockout