

**MXS4232C EXTRACTOR (HIGH VOLTAGE) 600G
BUT SET TO A MAXIMUM OF 335G
A1000 INVERTER (PROCESSING MATS)**

CONSTANT	VALUE	CONSTANT	VALUE
A1-00	0	E1-10	20/17
A1-01	2	E2-01	NOTE 1
A1-02	0	H1-01	40
A1-03	2220	H1-02	41
B1-01	0	H1-03	3
B1-02	1	H1-04	4
B1-03	0	H1-05	5
C1-01	60	H1-06	22
C1-02	30	H1-07	A
C1-04	30	H2-01	E
C6-01	0	H2-02	16
C6-02	1	H3-02	4
D1-01	3.3	H3-06	0
D1-02	6.2	H3-10	5
D1-03	19	L1-01	0
D1-04	58	L2-01	2
D1-05	76	L3-01	1
D1-06	76	L3-02	120
D1-17	4	L3-03	100
E1-01	460/400	L3-04	0
E1-03	F	L3-05	0
E1-04	76	L3-06	150
E1-05	460/400	L4-03	70
E1-06	60	L4-04	10
E1-07	3	L8-05	0
E1-08	30/25	L8-07	0
E1-09	1.5		

NOTE 1: Enter Ampere rating of inverter
 NOTE2: Wire motor 380V for 380V – 415V
 Wire motor 440V for 440V – 480V

Release Date: June 9, 2014 Revision: C